

# Specificaties SRK-ZSX Wandmodel

SRK/SRC		20ZSX-W (B)(T)	25ZSX-W (B)(T)	35ZSX-W (B)(T)	50ZSX-W (B)(T)	60ZSX-W (B)(T)
<b>PRESTATIES KOELEN</b>						
Capaciteit	kW	2,0(0,9-3,4)	2,5(0,9-3,87)	3,5(0,9-4,5)	5,0(1,0-6,2)	6,1(1,0-6,9)
Opgenomen vermogen	kW	0,31	0,44	0,74	1,24	1,87
S.E.E.R.		10,0	10,3	9,5	8,3	7,8
Energie label		A+++	A+++	A+++	A++	A++
Werkbereik	°C	-15 tot +46	-15 tot +46	-15 tot +46	-15 tot +46	-15 tot +46
<b>PRESTATIES VERWARMEN</b>						
Capaciteit	kW	2,7(0,8-5,5)	3,2(0,8-6,0)	4,3(0,8-6,8)	6,0(0,8-8,2)	6,8(0,8-8,8)
Capaciteit (-10°C)	kW	2,8	3,0	3,4	4,5	5,2
Opgenomen vermogen	kW	0,47	0,59	0,90	1,36	1,65
S.C.O.P.		5,2	5,2	5,1	4,7	4,7
Energie label		A+++	A+++	A+++	A++	A++
Werkbereik	°C	-20 tot +24	-20 tot +24	-20 tot +24	-20 tot +24	-20 tot +24
<b>GEGEVENS BINNENDEEL</b>						
		<b>SRK20ZSX-W (B)(T)</b>	<b>SRK25ZSX-W (B)(T)</b>	<b>SRK35ZSX-W (B)(T)</b>	<b>SRK50ZSX-W (B)(T)</b>	<b>SRK60ZSX-W (B)(T)</b>
Luchthoeveelheid laag/hoog	m <sup>3</sup> /h	360/678	402/732	438/786	468/858	534/978
Geluidsdruk u-laag/hoog*	dB(A)	19/38	19/39	19/43	22/44	22/48
Afmetingen (HxBxD)	mm	305x920x220	305x920x220	305x920x220	305x920x220	305x920x220
Gewicht	kg	13,0	13,0	13,0	13,0	13,0
Condensaansluiting	mm	16	16	16	16	16
<b>GEGEVENS BUITENDEEL</b>						
		<b>SRC20ZSX-W</b>	<b>SRC25ZSX-W</b>	<b>SRC35ZSX-W</b>	<b>SRC50ZSX-W2</b>	<b>SRC60ZSX-W1</b>
Luchthoeveelheid	m <sup>3</sup> /h	1860	1860	2160	2340	2490
Geluidsdruk (silent mode)*	dB(A)	43(33)	44(35)	48(38)	51(42)	52(42)
Afmetingen (HxBxD)	mm	640x871x290	640x871x290	640x871x290	640x871x290	640x871x290
Gewicht	kg	43,5	43,5	43,5	45,0	45,0
Voeding	V/pH/Hz	220-240/1/50-60	220-240/1/50-60	220-240/1/50-60	220-240/1/50-60	220-240/1/50-60
Koudemiddel		R32	R32	R32	R32	R32

\*De vermelde geluidsniveaus zijn gemeten op 1 meter van de airconditioner