

## Providing high efficiency and comfort

- › Whisper quiet in operation down to 20 dBA
- › Online controller (optional): control your indoor from any location with an app, via your local network or internet and keep an overview on your energy consumption
- › The unit's compact dimensions makes it ideal for renovation projects, especially for above door installation
- › Seasonal efficiency values up to A++ in cooling and heating
- › Space saving contemporary wall mounted design



FTXP-K3 + RXP-K3

BLUEEVOLUTION

Efficiency data	Seasonal efficiency (according to EN14825)							Indoor unit		Outdoor unit	Refrigerant		
	Cooling capacity	Heating capacity	Energy label	Pdesign	SEER	SCOP	Annual energy consumption	Dimensions	Sound power level	Sound power level	Type/GWP	Charge (kg/TCO <sub>2</sub> Eq)	
	Min./Nom./Max. (kW)	Min./Nom./Max. (kW)	Cooling/Heating	Cooling/Heating (kW)	Cooling	Heating	Cooling/Heating (kWh)	H x W x D (mm)	Cooling/Heating (dBA)	Cooling/Heating (dBA)			
20	2.00	2.50	A++/A++	2.00/2.20	6.79	4.65	103/662	286x770x225	55/55	46/47	R-32/ 675	0.76/0.52	
25	2.50	3.00		2.50/2.40	6.92	4.61	126/728		55/55				
35	3.50	4.00		3.50/2.80	6.64	4.64	185/845		58/58	48/48			
50	5.0	6.0	A++/A+	5.00/4.60	6.72	4.10	260/1,571	295x990x263	59/61	47/49			1.40/0.95
60	6.0	7.0		6.00/4.80	6.82		308/1,640		60/62	49/49			1.45/0.98
71	7.1	8.2	A/A	7.10/6.20	5.30	3.81	469/ 2,279		62/62	52/52			1.15/0.78

Contains fluorinated greenhouse gases